

# pH::lyser



pH::lyser eco monitors pH & temperature

pH::lyser pro: high temperature range

- s::can plug & measure
- measuring principle: unique, non-porous / non-leaking combined reference electrode for technically unrivalled and consistent pH performance
- multiparameter sensor
- ideal for surface water, ground water, drinking water and waste water
- long term stable and maintenance free in operation
- factory precalibrated
- mounting and measurement directly in the media (InSitu) or in a flow cell
- operation via s::can terminals & s::can software
- optional: automatic cleaning with compressed air
- plug connection or fixed cable

## recommended accessories

part number	article name
C-1-010-sensor	1 m connection cable for s::can physical and ISE probes
D-315-xxx	con::cube
D-320-xxx	con::lyte
F-12-sensor	carrier s::can physical probes
F-45-four	flow cell for four s::can physical probes
F-46-four-iscan	i::scan flow cell for up to 3 additional s::can probes
F-45-sensor	flow cell for s::can sensor
S-11-xx-moni	moni::tool Software



### technical specification

measuring principle	potentiometric	housing material	stainless steel 1.4404/1.4401, POM-C
measuring principle detail	combined, non-porous reference electrode		or stainless steel 1.4404/1.4401, PVC (E-514-4-075)
resolution	0.01 pH	weight (min.)	400 g
accuracy (standard solution)	0.1 pH	dimensions (Ø x l)	33 x 257 mm
automatic compensation instrument	temperature	operating pressure	0 ... 10 bar
response time (T90)	30 ... 0 sec.	installation / mounting	submersed or in a flow cell
integrated temperature sensor	0 ... 90 °C	process connection	quick connect
integration via	con::cube con::lyte con::nect	flow velocity	3 m/s (max.) 0.01 m/s (min.)
power supply	9 ... 18 VDC	automatic cleaning	media: compressed air permissible pressure: 3 ... 6 bar
power consumption (typical)	0.8 W	conformity - EMC	EN 61326-1
power consumption (max.)	1 W	conformity - safety	EN 61010-1
interface to s::can terminals	sys plug (IP67), RS485	operating temperature (eco)	0 ... 70 °C
cable length	7.5 m fixed cable (-075) or plug connection (-000)	operating temperature (pro)	0 ... 90 °C
cable type	PU jacket	storage temperature (electrode)	-5 ... 30 °C
		storage temperature (sensor)	-10 ... 60 °C
		protection class (-000)	IP67
		protection class (-075)	IP68

### measuring range

		parameter		part number
		pH [pH]	temperature [°C]	
pH::lyser eco (pH, temp)	min.	2	0	E-514-2-000 / -075
	max.	12	70	
pH::lyser pro (pH, temp)	min.	0	0	E-514-3-000 / -075
	max.	13	90	